

2022 CATALOG



VERCELLI

PERFORMANCE TIRES

OWN THE ROAD



ABOUT US

Designed by drivers, for drivers, Vercelli tires are the perfect fusion of style and performance. Whether you want low-profile, high-performance, off-road, or classic white-wall tires, we have the solution to meet any budget. We are committed to providing a high-quality, high-performance tire at a price attainable to all drivers. Backed by our exclusive No Questions Asked 25/365 Free Replacement Limited Protection Policy, it has never been easier to Own The Road.





VERCELLI
PASSENGER
TIRES





A premium, all-season grand touring power design featuring a quiet ride, the STRADA I is developed with VDMS – Variable Depth Micro-Positioned Siping – technology that provides superior handling and enhanced traction on all road surfaces. The STRADA I shoulders are designed with an alternating closed buttress area for an exceptionally quiet ride while ensuring long, trouble-free mileage. Our No Questions Asked, 25/365 Free Replacement Limited Protection Policy includes FREE one-year replacement from date of purchase plus a **60,000-mile** usable tread life expectancy.

STRADA I

25/365
WARRANTY
FREE REPLACEMENT | NO QUESTIONS ASKED
2012-2014 model years only. See retailer for details.

Size	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PSI	UTQG	Stock #
235/70R17	109T	10.5	30.00	9.45	2271@50	500AB	VC639
265/70R18	116T	10.5	32.64	10.71	2756@44	500AB	VC659
195/65R15	91H	10	25.00	7.91	1356@44	500AA	VC605
205/65R15	94H	10	25.47	8.23	1477@44	500AA	VC615
225/65R16	100T	10	27.48	9.00	1764@44	500AB	VC648
215/65R17	99V	10	28.03	8.70	1709@44	500AA	VC651
225/65R17	106V	10	28.50	8.98	2094@50	500AA	VC640
235/65R17	104H	10	29.06	9.45	1984@44	500AA	VC638
235/65R18	106T	10	30.04	9.45	2094@44	500AB	VC656
255/65R18	111T	10	31.06	10.24	2403@44	500AA	VC674
265/65R18	114T	10	31.54	10.71	2601@44	500AB	VC658
275/65R18	116T	10.5	32.09	10.98	2756@44	500AB	VC657
195/60R15	88H	10	24.21	7.91	1235@44	500AA	VC600
205/60R15	91H	10	24.69	8.23	1356@44	500AA	VC603
205/60R16	92H	10	25.67	8.19	1389@44	500AA	VC620
215/60R16	95V	10	26.14	8.70	1521@44	500AA	VC630
225/60R16	98H	10	26.61	8.98	1653@44	500AA	VC625
225/60R17	99H	10	27.64	8.98	1709@44	500AA	VC645
235/60R17	106H	10	28.11	9.45	2094@50	500AA	VC644
235/60R18	107H	10	29.09	9.45	2149@50	500AA	VC671
245/60R18	105H	10	29.57	9.76	2039@44	500AA	VC672
265/60R18	110H	10	30.51	10.71	2336@44	500AA	VC677
255/60R19	109H	10	31.06	10.24	2271@44	500AA	VC660
275/60R20	115T	10	32.99	10.98	2679@44	500AB	VC686
195/55R15	85V	10	23.43	7.91	1135@44	500AA	VC610
205/55R16	94V	10	24.88	8.43	1477@50	500AA	VC602
215/55R16	97V	10	25.28	8.90	1609@50	500AA	VC622
215/55R17	98V	10	26.30	8.90	1653@50	500AA	VC650
225/55R17	101V	10	26.77	9.17	1819@50	500AA	VC646
235/55R17	99V	10.5	27.17	9.65	1709@44	500AA	VC637



A premium, all-season grand touring power design featuring a quiet ride, the STRADA I is developed with VDMS – Variable Depth Micro-Positioned Siping – technology that provides superior handling and enhanced traction on all road surfaces. The STRADA I shoulders are designed with an alternating closed buttress area for an exceptionally quiet ride while ensuring long, trouble-free mileage. Our No Questions Asked, 25/365 Free Replacement Limited Protection Policy includes FREE one-year replacement from date of purchase plus a **60,000-mile** usable tread life expectancy.

STRADA I

cont.



Size	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PSI	UTQG	Stock #
225/55R18	102V	10	27.76	9.17	1874@50	500AA	VC661
235/55R18	104V	10	28.15	9.65	1984@50	500AA	VC669
255/55R18	109V	10	29.02	10.43	2270@50	500AA	VC673
225/55R19	99V	10.5	27.78	9.17	1709@44	500AA	VC692
235/55R19	105V	10.5	29.17	9.65	2039@50	500AA	VC691
245/55R19	103H	10.5	29.65	9.96	1929@44	500AA	VC690
275/55R20	113H	10.5	31.89	11.18	2535@44	500AA	VC675
215/50R17	95V	10	25.51	8.90	1521@50	500AA	VC635
225/50R17	98V	10	25.90	9.20	1653@50	500AA	VC652
235/50R17	100V	10	26.30	9.65	1764@50	500AA	VC641
225/50R18	95V	10	26.89	9.20	1520@44	500AA	VC654
235/50R18	101H	9	27.28	9.65	1819@50	500AA	VC667
235/50R18	101W	9	27.28	9.65	1819@50	500AA	VC668
255/50R19	107H	10.5	29.09	10.43	2149@50	500AA	VC695
245/50R20	102V	10	29.69	10.00	1874@44	500AA	VC662
255/50R20	109V	10.5	30.08	10.43	2271@50	500AA	VC663
265/50R20	107V	10.5	30.47	10.91	2149@44	500AA	VC664
225/45R18	95V	10	25.94	8.86	1521@50	500AA	VC643
235/45R18	98V	10	26.34	9.29	1653@50	500AA	VC665
245/45R18	100V	10	26.65	9.57	1764@50	500AA	VC670





A performance-driven premium tire with all-season capabilities, the STRADA II's unique engineering features a twin-type center rib design for high-speed stability and sure-footed braking. The tread design provides both a quiet ride and ultra-confident handling. Backed by our No Questions Asked, 25/365 Free Replacement Limited Protection Policy and a **45,000-mile** usable tread life expectancy.

STRADA II



Series	Size	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PSI	UTQG	Stock #
55	205/55ZR16	94W	10	24.88	8.43	1477@49	500AA	VC265
55	215/55ZR16	97W	10	25.28	8.90	1609@49	500AA	VC266
55	215/55ZR17	98W	10	26.30	8.90	1653@49	500AA	VC240
55	225/55ZR17	101W	10	26.77	9.17	1819@49	500AA	VC241
50	205/50ZR17	93W	10	25.12	8.43	1433@49	500AA	VC282
50	215/50ZR17	95W	10	25.51	8.90	1521@49	500AA	VC235
50	225/50ZR17	98W	10	25.91	9.17	1653@49	500AA	VC285
50	235/50ZR17	100W	10	26.30	9.65	1764@49	500AA	VC286
45	215/45ZR17	91W	10	24.65	8.39	1356@49	500AA	VC275
45	225/45ZR17	94W	10	24.96	8.86	1477@49	500AA	VC277
45	235/45ZR17	97W	10	25.35	9.29	1609@49	500AA	VC279
45	245/45ZR17	99W	10	25.67	9.57	1709@49	500AA	VC280
45	225/45ZR18	95W	10	25.94	8.86	1521@49	500AA	VC296
45	235/45ZR18	98W	10	26.34	9.29	1653@49	500AA	VC291
45	245/45ZR18	100W	10	26.65	9.57	1764@49	500AA	VC298
45	255/45R18	103W	10	27.05	10.04	1929@49	500AA	VC301
45	255/45R19	104Y	10	28.07	10.04	1984@49	500AA	VC302
45	245/45ZR20	103W	10	28.66	9.57	1929@49	500AA	VC320
45	255/45R20	103W	10	28.66	9.57	1929@49	500AA	VC304
40	205/40ZR17	84W	10	23.46	8.35	1102@49	500AA	VC270
40	235/40R17	90W	10	24.41	9.49	1477@49	500AA	VC313
40	245/40ZR17	95W	10	24.72	9.76	1521@49	500AA	VC281
40	275/40R17	98W	10	25.67	10.94	1653@49	500AA	VC317
40	215/40R18	89W	10	24.76	8.58	1279@49	500AA	VC274
40	225/40ZR18	92W	10	25.08	9.06	1389@49	500AA	VC295
40	235/40R18	95Y	10	25.39	9.49	1521@49	500AA	VC278





A performance-driven premium tire with all-season capabilities, the STRADA II's unique engineering features a twin-type center rib design for high-speed stability and sure-footed braking. The tread design provides both a quiet ride and ultra-confident handling. Backed by our No Questions Asked, 25/365 Free Replacement Limited Protection Policy and a **45,000-mile** usable tread life expectancy.

STRADA II

cont.



Series	Size	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PSI	UTQG	Stock #
40	245/40ZR18	97W	10	25.71	9.76	1609@49	500AA	VC297
40	255/40ZR18	99W	10	26.02	10.24	1709@49	500AA	VC299
40	225/40R19	93Y	10	26.10	8.59	1433@49	500AA	VC293
40	235/40R19	96W	10	26.42	9.25	1565@49	500AA	VC315
40	245/40R19	98Y	10	26.69	9.80	1653@49	500AA	VC294
40	245/40ZR20	99W	10	27.72	9.76	1709@49	500AA	VC340
40	275/40ZR20	106W	10	28.66	10.94	2094@49	500AA	VC318
35	215/35ZR18	84W	10	23.90	8.58	1102@49	500AA	VC290
35	255/35ZR18	94W	10	25.00	10.24	1477@49	500AA	VC255
35	265/35ZR18	97W	10	25.31	10.67	1609@49	500AA	VC267
35	275/35ZR18	99W	10	25.55	10.94	1709@49	500AA	VC268
35	225/35R19	88W	10	25.24	9.06	1235@49	500AA	VC311
35	255/35R19	96W	10	26.02	10.24	1565@49	500AA	VC256
35	225/35ZR20	90W	10	26.22	9.06	1323@49	500AA	VC312
35	245/35ZR20	95W	10	26.77	9.76	1521@49	500AA	VC310
35	255/35ZR20	97W	10	27.01	10.24	1609@49	500AA	VC316
35	275/35ZR20	102W	10	27.56	10.94	1874@49	500AA	VC330
30	265/30R19	93W	10	25.32	10.67	1433@49	500AA	VC348
30	275/30R19	96W	10	25.55	10.94	1565@49	500AA	VC269
30	225/30ZR20	85W	10	25.35	9.06	1135@49	500AA	VC305
30	235/30ZR22	90W	10	27.60	9.49	1323@49	500AA	VC322
30	245/30ZR22	92W	10	27.83	9.76	1389@49	500AA	VC325
30	265/30ZR22	97W	10	28.31	10.67	1609@49	500AA	VC350
30	295/30R22	103W	10.50	29.02	11.61	1929@49	500AA	VC448
25	295/25R22	97W	10.50	27.80	11.61	1609@49	500AA	VC446





A premium ultra-modern and performance-oriented design, the STRADA IV is built for today's Sport Utility Vehicles and Pickup Trucks. The STRADA IV has large shoulder elements that support the necessary extra load and steering control requirement for modern trucks and SUVs. The plus-sizing options are unique to Vercelli Tires. Backed by our No Questions Asked, 25/365 Free Replacement Limited Protection Policy and our **45,000-mile** usable tread life expectancy.

STRADA IV



Series	Size	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PSI	UTQG	Stock #
55	275/55R20	117V	10	31.89	11.18	2833@49	500AA	VC411
50	285/50R20	116V	10	31.26	11.69	2756@49	500AA	VC412
45	275/45R20	110V	10	29.76	10.75	2337@49	500AA	VC410
45	275/45R22	112V	10	31.77	10.75	2469@49	500AA	VC430
45	285/45R22	114V	10	32.09	11.22	2601@49	500AA	VC431
45	305/45R22	118V	10	32.80	11.93	2910@49	500AA	VC434
40	275/40ZR20	106V	10	28.66	10.94	2094@49	500AA	VC405
40	265/40R22	106W	10	30.35	10.67	2094@49	500AA	VC420
40	305/40R22	114V	10	31.61	12.32	2601@49	500AA	VC424
35	265/35R22	102V	10	29.33	10.67	1874@49	500AA	VC415
35	295/35R24	110V	10	32.13	11.85	2337@49	500AA	VC441
35	305/35R24	112V	10	32.44	12.32	2469@49	500AA	VC440
30	295/30ZR22	103W	10	29.02	11.85	1929@49	500AA	VC414
30	255/30ZR24	97W	10	30.08	10.24	1609@49	500AA	VC439
25	275/25ZR24	96W	10	29.45	11.14	1565@49	500AA	VC438





VERCELLI
CLASSIC TIRES





The CLASSIC 787 is a traditional all-season white sidewall design featuring slotted shoulders and a wear-resistant tread compound for trouble-free mileage and a quiet ride. The wide, longitudinal grooves provide good handling on both wet and dry surfaces while the flexible body design improves ride comfort. Backed by our No Questions Asked, 25/365 Free Replacement Limited Protection Policy.

CLASSIC 787



Series	Size	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PSI	UTQG	Stock #
75	P195/75R14	92S	10.5	25.51	7.72	1400@44	440AB	VC001
75	P205/75R14	95S	10.5	26.14	7.99	1532@44	440AB	VC003
75	P215/75R14	98S	10.5	26.69	8.50	1664@44	440AB	VC005
75	P205/75R15	97S	10.5	27.13	7.99	1598@44	440AB	VC030
75	P215/75R15	100S	10.5	27.68	8.50	1742@44	440AB	VC039
75	P225/75R15	102S	10.5	28.31	8.78	1874@44	440AB	VC048
75	P235/75R15	105S	10.5	28.86	9.25	2028@44	440AB	VC058
70	* P205/70R14	93S	10.5	25.35	8.23	1433@44	440AB	VC009
70	* P215/70R14	96S	10.5	25.91	8.70	1554@44	440AB	VC008
70	* P205/70R15	95S	10.5	26.34	8.23	1499@44	440AB	VC012
70	P215/70R15	97S	10.5	26.89	8.70	1620@44	440AB	VC015
70	P225/70R15	100S	10.5	27.44	8.98	1753@44	440AB	VC020

* Tires only available with black sidewall



vercellitire.com





VERCELLI
LIGHT TRUCK
TIRES






The all-new Terreno A/T is designed to provide on-road performance with off-road durability. The offset chevron grooves provide added traction in mud, dirt, and other soft surface terrain. Optimized siping provides improved wet traction, element flexibility and severe weather rated snow traction. The variable pitch pattern reduces noise propagation to provide a quiet and comfortable ride. Back by our No Questions Asked, 25/365 Free Replacement Limited Protection Policy and a **50,000-mile** treadwear protection, the Terreno A/T is ready for your next adventure.



TERRENO A/T

Size	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PSI	UTQG	Stock #
235/75R15	105	13	28.86	9.25	2039@44	500AA	VC1010
245/75R16	111	13	30.47	9.76	2403@44	500AA	VC1035
265/70R16	112	13	30.63	10.71	2469@44	500AA	VC1080
265/75R16	116	13	31.65	10.51	2756@44	500AA	VC1065
245/65R17	107	13	29.53	9.76	2149@44	500AA	VC1030
245/70R17	110	13	30.55	9.76	2337@44	500AA	VC1050
265/70R17	115	13	31.65	10.71	2679@44	500AA	VC1085
265/70R18	116	13	32.64	10.71	2756@44	500AA	VC0517
275/65R18	116	13	32.09	10.98	2756@44	500AA	VC0518
275/55R20	117	13	31.89	11.18	2833@49	500AA	VC1105
275/60R20	115	13	32.99	10.98	2679@44	500AA	VC0519
LT235/75R15	104/101	13	28.86	9.25	1985/1820@50	-	VC1015
LT235/85R16	120/116	13	31.73	9.25	3042/2778@80	-	VC1020
LT215/85R16	115/112	14	30.39	8.50	2680/2470@80	-	VC1005
LT225/75R16	115/112	14	29.29	8.78	2680/2470@80	-	VC1000
LT245/75R16	120/116	16	30.47	9.76	3042/2778@80	-	VC1040
LT265/75R16	123/120	16	31.65	10.51	3415/3085@80	-	VC1070
LT285/75R16	126/123	17	32.83	11.26	3750/3415@80	-	VC0436
LT235/80R17	120/117	14	31.81	9.25	3085/2835@80	-	VC0650
LT245/75R17	121/118	16	31.50	9.76	3195/2910@80	-	VC1055
LT265/70R17	121/118	16	31.65	10.71	3195/2910@80	-	VC1090
LT285/70R17	121/118	17	32.76	11.50	3195/2910@80	-	VC1110
31X10.50R15LT	109	14	30.51	10.55	2270@50	-	VC1095
35X12.50R20LT	121	16	34.53	12.52	3195@65	-	VC1120





Mud, dirt, and rough terrain are no match for the all new Terreno M/T. This highly aggressive dual pitch pattern provides excellent off-road performance. The 3-ply sidewall and integrated stone ejectors protect while optimized siping provides flexibility without sacrificing durability. A deep buttress area provides additional traction in soft surfaces. Back by our No Questions Asked, 25/365 Free Replacement Limited Protection Policy, the Terreno M/T is ready for the path less traveled.



TERRENO M/T



Size	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PSI	Stock #
LT235/75R15	110/107S	18	28.86	9.25	2335/2150@65	VC2467
LT265/75R16	123/120Q	18	31.65	10.51	3415/3085@80	VC2457
LT285/75R16	126/123R	19.5	32.83	11.26	3750/3415@80	VC2459
LT315/75R16	127/124Q	19.5	34.57	12.32	3860/3525@65	VC2484
LT265/70R17	121/118Q	19.5	31.65	10.71	3195/2910@80	VC2461
LT285/70R17	121/118Q	19.5	32.76	11.50	3195/2910@80	VC2473
LT295/70R17	121/118Q	19.5	33.31	11.77	3195/2910@80	VC2454
LT275/65R18	123/120Q	19.5	32.09	10.98	3415/3085@80	VC2492
LT275/70R18	125/122Q	19.5	33.19	10.98	3640/3305@80	VC2472
31X10.50R15LT	109Q	18	30.52	10.54	2270@50	VC2463
32X11.50R15LT	113Q	19.5	31.52	11.42	2535@50	VC2496
33X12.50R15LT	108Q	20	32.52	12.50	2205@35	VC2465
35X12.50R15LT	113Q	20	34.52	12.50	2535@35	VC2498
33X12.50R17LT	114Q	19.5	32.52	12.50	2600@50	VC2300
35X12.50R17LT	121Q	20	34.52	12.50	3195@65	VC2466
33X12.50R18LT	122Q	20	32.52	12.50	3305@80	VC2477
35X12.50R18LT	128Q	20	34.52	12.50	3970@80	VC2478
33X12.50R20LT	119Q	19	32.52	12.50	3000@80	VC2480
35X12.50R20LT	125Q	20	34.52	12.50	3640@80	VC2479
33X12.50R22LT	114R	19.5	32.52	12.50	2600@80	VC2304
35X12.50R22LT	121Q	19.5	34.52	12.50	3195@80	VC2483
37X13.50R22LT	128Q	19.5	36.52	13.58	3970@80	VC2487





The workhorse of the Vercelli line, the Terreno H/T & H/S is designed to be durable and dependable. The modern dual pitch (A/B) pattern provides a quiet and comfortable ride with consistent, long-lasting performance. Large circumferential grooves evacuate water for improved traction in the rain. Optimized siping provides excellent traction and braking performance in wet and light snow conditions. A solid center and shoulder elements provide responsive handling and stability. Back by our No Questions Asked, 25/365 Free Replacement Limited Protection Policy and a **50,000-mile** treadwear protection, the Terreno H/T & H/S is ready to work.



TERRENO H/S

Size	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PSI	UTQG	Stock #
215/70R16	100H	10	27.87	8.70	1764@44	500AA	VC0690
225/70R16	103H	10	28.43	8.98	1929@44	500AA	VC0700
235/70R16	106H	10	28.98	9.45	2094@44	500AA	VC0710
245/70R16	107H	10	29.53	9.76	2149@44	500AA	VC0720
255/70R16	111H	10	30.08	10.24	2403@44	500AA	VC0331
265/70R16	112T	10	30.63	10.71	2469@44	500AA	VC0730
225/65R17	102H	10	28.50	8.98	1874@44	500AA	VC0760
235/65R17	108H	10	29.06	9.45	2205@49	500AA	VC0770
245/65R17	107H	10	29.53	9.76	2149@44	500AA	VC0790
245/70R17	110H	10	30.55	9.76	2337@44	500AA	VC0800
265/65R17	112H	10	30.55	10.71	2469@44	500AA	VC0810
265/70R17	115H	10	31.65	10.71	2679@44	500AA	VC0820
235/55R18	104V	10	28.15	9.65	1984@49	500AA	VC0830
255/65R18	111T	10	31.06	10.24	2403@44	500AA	VC0391
265/60R18	110H	10	30.51	10.71	2337@44	500AA	VC0850
275/55R20	117H	11	31.89	11.18	2833@49	500AA	VC0870



TERRENO H/T

Size	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PSI	UTQG	Stock #
LT215/85R16	115/112S	13	30.39	8.50	2680/2470@80	-	VC2000
LT225/75R16	115/112S	13	29.29	8.78	2680/2470@80	-	VC2020
LT235/85R16	120/116S	13	31.73	9.25	3042/2778@80	-	VC2010
LT245/75R16	120/116S	13	30.47	9.76	3042/2778@80	-	VC2030
LT265/75R16	123/120S	13	31.65	10.51	3415/3085@80	-	VC2040
LT245/70R17	119/116S	13	30.55	9.76	3000/2755@80	-	VC2042
LT245/75R17	121/118S	13	31.50	9.76	3195/2910@80	-	VC2041
LT265/70R17	121/118S	13	31.65	10.71	3195/2910@80	-	VC2044
LT275/70R18	125/122S	15	33.19	10.98	3640/3305@80	-	VC2046

VERCELLI

LIMITED PROTECTION POLICY

Thank you for your interest in Vercelli brand tires for your vehicle. We are proud of the quality and performance of the wide range of Vercelli products and we understand that your continued satisfaction is essential to our success.

ELIGIBILITY

This Limited Protection Policy applies to Vercelli brand passenger and light truck tires purchased on or after January 1, 2020, or, in the absence of proof of purchase, tires with a manufacturing DOT code reading DOT 0120 or later. Eligible tires are covered by this Limited Protection Policy for up to 60 months from the date of purchase or tire manufacturer date. This Limited Protection Policy applies to the original owner of new Vercelli branded passenger and light truck tires that are operated in normal service, and used on the same vehicle on which they were originally installed according to the vehicle manufacturer's recommendations. Only Vercelli tires purchased and operated in the United States and Canada are covered by this Limited Protection Policy.

WHAT IS COVERED BY OUR EXCLUSIVE NO QUESTIONS ASKED, 25/365 FREE REPLACEMENT LIMITED PROTECTION POLICY?

The Vercelli No Questions Asked, 25/365 Free Replacement Limited Protection Policy will fully cover (100% credit) all eligible Vercelli brand passenger and light truck tires should one become unserviceable due to defective workmanship, materials, road hazard or a condition other than those listed below during the first 25% of usable treadwear or one year from date of purchase, whichever occurs first.

Tires not eligible for the No Questions Asked, 25/365 Free Replacement Limited Protection Policy that are removed from service due to a covered condition will be replaced with a comparable new Vercelli brand tire on a prorated basis for a period up to 60 months from the date of purchase or tire manufacturer date, or when the treadwear indicators become visible (worn to 2/32"), whichever occurs first.

WHAT IS A COMPARABLE TIRE?

A comparable tire may be either the same line and pattern of tire or, in the event that the tire is not available, a tire of the same construction and quality with a different sidewall or tread configuration. If a higher priced tire is accepted as replacement, the difference in price will be at an additional charge to the owner. Any Vercelli brand replacement tire provided pursuant to this Limited Protection Policy will be covered by the Vercelli Limited Protection Policy in effect at the time of replacement.

MILEAGE COVERAGE PLAN

If an eligible tire wears down to the treadwear indicator bars (2/32") and the tire has not delivered the miles specified below, Vercelli will provide a prorated adjustment based on actual mileage delivered. The cost of mounting, balancing and any other service charges including applicable taxes are excluded from reimbursement.

Pattern	Coverage Plan (Miles/Km)	25/365	Workmanship & Materials (Mo.)
Strada I	60,000/100,000	Yes	60
Strada II	45,000/70,000	Yes	60
Strada IV	45,000/70,000	Yes	60
Classic 787	N/A	Yes	60
Terreno A/T	50,000/80,000	Yes	60
Terreno H/S	50,000/80,000	Yes	60
Terreno H/T	50,000/80,000	Yes	60
Terreno M/T	N/A	Yes	60

The Mileage Coverage Plan applies only to the original purchaser and the tires have been used only on the vehicle on which they were originally installed according to the vehicle manufacturer's recommendations. The Mileage Coverage Plan does not apply to tires used in commercial applications. Tires that have not been rotated at least every 6,000 miles as evidenced by a completed rotation schedule are excluded. Likewise, tires in service for more than 60 months regardless of mileage attained are excluded.

WHAT IS NOT COVERED BY THE LIMITED PROTECTION POLICY?

(1) Improper operation or maintenance. This includes, but is not limited to, effects caused by improper tire inflation and/or improper load/speed practices and/or improper or insufficient tire rotation. (2) Wear due to improper vehicle alignment including but not limited to, uneven, cupping,

irregular, spotty and feathering wear. (3) Deliberate abuse or vandalism. Ride or vibration complaint after the first 1/32" of treadwear. (4) Damage due to snow chain usage, improper mounting/dismounting or automotive accident. (5) Tires used in commercial applications are not eligible for 25/365 or Mileage coverage where applicable.

OWNER'S OBLIGATIONS

To make an eligible claim under this Limited Protection Policy, tires must be rotated with the prescribed rotation patterns as recommended be either the vehicle owner's manual or an authorized Vercelli tire dealer. Owner must present an original tire sales invoice indicating the date of purchase, tire description and odometer mileage. Adjustment tires must be presented to an authorized Vercelli dealer and those tires replaced become the property of Vercelli Tires. Installation charges such as mounting, dismounting and balancing as well as any applicable taxes and government-mandated charges on the services rendered at the time of adjustment is the owner's responsibility. Adjustment claims must be completed on an approved claim form, supplied by an authorized Vercelli dealer, and submitted at time of adjustment.

WHAT ARE YOUR LEGAL RIGHTS?

No Representative or Dealer has authority to make any representation, promise or agreement on behalf of Vercelli, except as stated herein.

Any tire, no matter how well constructed, may fail in service or otherwise become unserviceable due to conditions beyond the control of the tire manufacturer. Under no circumstances is this Limited Protection Policy a representation that a tire failure cannot occur. This Limited Protection Policy gives you specific legal rights and you may also have other rights that vary from state to state or province to province.

Disclaimer: This Limited Protection Policy is in lieu of, and Vercelli Tires hereby disclaims, any and all other Limited Protection Policies and representations, express or implied, including without limitation any Protection Policy of merchantability of fitness for a particular purpose, and no other Limited Protection Policy or representation of any kind is made by Vercelli Tires or shall be implied by law. This Limited Protection Policy is subject to change without notice.

Limitation of damages: In no event and under no circumstance shall Vercelli Tires be liable to the buyer for any indirect, special, incidental, consequential, lost profit, loss of business, loss of goodwill or reputation, punitive or other damage, cost (including for replacement transportation), expense or loss of any kind. Some states and provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

VERCELLI TIRE CARE AND MAINTENANCE GUIDE

Proper inflation pressure is essential for optimum tire performance, safety, and fuel economy. Check for proper inflation pressure at least monthly while tires are cool, as tires will warm up from use after a number of miles so it is best to check before driving. Use a quality handheld accurate air pressure gauge. It is best to occasionally have your Vercelli tires inspected by a professional tire shop, as it is difficult to tell just by looking at radial tires whether they are under-inflated or over-inflated. Furthermore, when operating a vehicle equipped with radial tires, it is difficult to notice when a tire has gone flat or nearly flat since the handling of the vehicle may not deteriorate significantly. Remember to always maintain inflation pressure at the level recommended by the vehicle manufacturer as shown on the vehicle placard, on the vehicle certification label or in the vehicle owner's manual.

Evidence of air loss or repeated under-inflation always requires expert inspection to determine the source of leakage and tire removal to determine repairability. To avoid injury, NEVER attempt to re-inflate a tire that has been in operation severely under-inflated. Progressive air loss may result from a variety of conditions such as punctures, cuts, curbing, impacts or partial bead unsealing. Some installation or fitment causes for air loss are (1) incomplete bead seating, (2) tearing of the tire bead caused by a machine tool due to insufficient lubrication or improper adjustment, (3) leaking valve core or rubber valve components. These should be corrected or replaced when problems are detected and/or whenever tires are replaced.

Under-inflation is the leading cause of tire failure and my result in severe cracking, component separation or complete loss of air. Under-inflation reduces tire load carrying capacity, allows for excessive sidewall flexing and increased rolling resistance, resulting in potential heat build-up and mechanical damage. Maintaining proper inflation pressure is the most important thing you can do to help promote tire safety, durability and maximize tread life.

Over-inflation will deteriorate ride quality, reduce braking ability and generate unwanted vibration. Over-inflation also increases the chances of impact damage.

DON'T OVERLOAD YOUR VEHICLE

The maximum load capacity stamped on the sidewalls of P-metric tires is reduced by ten percent when used on a light truck, utility vehicle or trailer. Never fit P-metric tires to light trucks that specify LT-type replacement tires.

VERCELLI

PERFORMANCE TIRES

VercelliTires.com

American Omni Trading Company

1221 Park West Green Dr. | Katy, TX 77493

Corporate Phone | 281-600-TIRE

american-omni.com